Photonics-USA

4207 Tylers Creek Ln.
Kents General Store, VA 23084
DUNS#: 623879116

sales@photonics-usa.com

FBT Coupler

1x3 Single Fused Dual Window Wideband Coupler

Specifications

Parameter		Premium	A Grade
Operating Wavelength Range		1311 & 1550 ± 40 nm	
Insertion Loss (Max)		≤ 5.6 dB	≤ 5.9 dB
Uniformity (Typical)		≤ 1.2 dB	≤ 1.6 dB
Return Loss		≥ 50 dB	
PDL		≤ 0.10 dB	≤ 0.15 dB
TDL		≤ 0.2 dB (-10°C ~ +75°C)	≤ 0.4 dB (-40°C ~ +85°C)
Operating & Storage Temperature		- 40° C ~ + 85° C	
Package Dimensions	Light Duty (B)	3.0mm (Φ) x 55.0mm (L)	
	Medium Duty (L)	3.0mm (Φ) x 70.0mm (L)	

Note1: All values specified are without connectors.
Note3: Fiber Type – Corning SMF-28e.

Ordering Information

D W W C – 1 3 – ___ – EVEN – ___ – ___ – ___ – ___

Port Number	Grade	Coupling Ratio	Wavelength	Fiber Length	Pigtail Style	Connector
13: 1 x 3	P: Premium A: A Grade	EVEN: 33/33/34	E: 1310 nm F: 1480 nm G: 1510 nm H: 1550 nm L: 1625 nm	1: 1 meter 2: 2 meter S: Special	(=Package style) B: bare fiber L: 900 μm loose tube	0: None 1: FC/PC 2: FC/APC 3: SC/ PC 4: SC/APC 5: FC/SPC 6: SC/SPC 7: LC/UPC 8: LC/SPC 9: Special A: FC/UPC B: SC/UPC C: ST